


Metal Bellows Coupling

with expanding clamps

optional
laserwelded
optional full stainless
steel versionoptional chem.
nickel-plated**Order Code****KB8 / 30****-****53****-****15****-****20****-****S**

Type / Size

Length
LØD1
(H7)ØD2
(f7)

Options

Size	Torque TKN (Nm)	Dimensions (mm)										Technical Data								
		L	Ø A	D1	D2	H	C	E	E1	B	F/G	Mass (kg)	Moment of Inertia J (g m²)	Spring Stiffness			Misalignment			max. speed (min-1)
		Length	Outer Ø	Bore Size (H7) min~max	(f7) min~max						Screw (ISO4762) TA (Nm)			torsional CT 10³ (Nm/rad)	radial CR (N/mm)	axial CA (N/mm)	radial ΔKr (mm)	axial ΔKa (mm)	angular ΔKw (°)	
18	18	45	45	10-25.4	13-25	17	5.5	17.5	20	47.4	M5	0.14	0.04	20	205	50	0.2	0.5	1.5	12800
		52									8	0.15	0.05	15	82	35	0.25	0.5	2	12800
30	30	53	56	10-32	14-30	20	7.5	24.5	25	56.4	M6	0.30	0.15	38	720	50	0.15	0.6	1.5	10300
		61		#30							15	0.31	0.16	28	225	28	0.25	1.0	2	10300
60	60	62	66	12-35	23-38	23	10	29	27	66	M8	0.40	0.28	75	1150	90	0.15	0.6	1.5	8700
		72									40	0.42	0.31	50	340	50	0.25	1.0	2	8700
150	150	71	82	14-44	26-42	28	11	33.5	32	82.9	M10	0.80	0.90	155	2020	145	0.2	0.5	1.5	6900
		83									84	0.85	0.95	105	595	85	0.25	0.5	2	6900
300	300	84	110	20-60	38-60	39	13	38	45	110	M12	1.62	3.28	502	6300	280	0.2	0.5	1.5	6000
		98									145	1.66	3.37	285	1400	145	0.25	0.8	2	6000
500	500	87.5	122	25-70	58-80	42	15	42	50	122	M12	3.33	5.32	690	7790	100	0.2	0.5	1.5	5000
		98.5									145	3.43	5.43	320	970	85	0.25	1	2	5000

**Material**bellows – stainless steel
collet clamps - aluminium
expanding clamps - steel**Hub and Hollow Shaft**

bore tolerance: H7

Keywayoptional acc. DIN 6885
biggest bore marked with a #**Temperature Range**

-30 °C ~ 120 °C