

T4A71B-4 0,37KW 230/400V B14

Three-phase asynchronous motor in aluminum

Motor type T4A71B-4 0,37KW 230/400V B14
 Brand BUSCK
 Item number 43040723

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,37	50	1,74	1430
400	0,37	50	1,00	1430
460	0,43	60	1,00	1716

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	81,1
Insulation class	F	Efficiency, load 75%	80,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	77,2
Max. ambient temp.	45°C	Power fact, load 100%	0,66
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	8
Torque, Nm	2,5745	Sound pressure Lp dB(A)	55
Starting torque ratio	3,4	Bearing DE	6204-2Z/C3
Pull up torque ratio	3,0	Bearing NDE	6204-2Z/C3
Pull out torque ratio	3,6	Balance grade	Normal
Starting current ratio	6,2	Inertia kgm ²	0,001188
This motor has DNV type approval		Cable entries	1xM20

Note Termokontakt
IE4

