

Type K - Efficiency data

Permissible power P1 [kw] and rated output torque M2 [Nm]													
Ratio	Input rpm.	Gear sizes											
		20		25		30		35		40		50	
		P1	M2	P1	M2	P1	M2	P1	M2	P1	M2	P1	M2
		kw	Nm	kw	Nm	kw	Nm	kw	Nm	kw	Nm	kw	Nm
01:01:00	10	0,083-75		0,12-110		0,22-200		0,42-380		0,77-700		1,1-1000	
	100	0,8-72		1,2-108		2,2-200		4,1-375		7,4-670		10,8-980	
	250	1,9-69		2,8-104		5,4-195		10,0-362		16,5-600		25,6-930	
	500	3,4-62		5,5-100		9,9-180		17,0-308		30,3-550		46,3-840 *	
	750	4,8-58		7,5-91		14,0-170 *		24,0-170 *		43,0-520 *		64,5-780 *	
	1000	5,7-52		9,1-83 *		18,2-165 *		30,2-274 *		52,3-475 *		80,5-730 *	
	1500	7,8-47 *		12,4-75 *		24,8-150 *		41,0-248 *		69,4-420 *		111-675 *	
	2000	8,8-40 *		15,4-70 *		30,8-140 *		46,7-212 *					
	3000	10,5-32 *		21,5-65 *									
02:01:00	10	0,04-76		0,06-114		0,11-210		0,21-380		0,38-700		0,58-1050	
	100	0,4-72		0,6-110		1,1-206		2,1-376		3,75-680		5,5-990	
	250	0,96-70		1,4-104		2,7-196		5,0-365		8,5-620		13,0-940	
	500	1,8-68		2,8-100		5,0-184		8,5-310		15,4-560		23,3-845 *	
	750	2,7-66		3,8-92		7,0-170 *		12,2-295 *		22,0-530 *		32,2-780 *	
	1000	3,5-64		4,8-88 *		9,0-164 *		15,2-275 *		26,4-480 *		40,5-735 *	
	1500	5,1-62 *		6,7-82 *		12,4-150 *		20,6-250 *		35,1-425 *		56,2-680 *	
	2000	6,3-57 *		8,5-77 *		15,4-140 *		25,6-233 *					
	3000	8,9-54 *		12-73 *									